

US006747646B2

(12) United States Patent Gueziec et al.

(10) Patent No.: US 6,747,646 B2

(45) **Date of Patent: Jun. 8, 2004**

(54) SYSTEM AND METHOD FOR FUSING THREE-DIMENSIONAL SHAPE DATA ON DISTORTED IMAGES WITHOUT CORRECTING FOR DISTORTION

(75) Inventors: Andre Gueziec, Mamaroneck, NY (US); Alan David Kalvin, Irvington, NY (US); Willie Williamson, Jr., Roseville, CA (US); Kenong Wu,

Davis, CA (US)

(73) Assignee: International Business Machines Corporation, Armonk, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 573 days.

(21) Appl. No.: 09/852,739

(22) Filed: May 11, 2001

(65) **Prior Publication Data**

US 2001/0021806 A1 Sep. 13, 2001

Related U.S. Application Data

- (62) Division of application No. 09/354,800, filed on Jul. 16, 1999, now Pat. No. 6,415,171.
- (51) Int. Cl.⁷ G06T 15/00

(56) References Cited

U.S. PATENT DOCUMENTS

5,299,288 A	*	3/1994	Glassman et al	700/245
5,445,166 A	*	8/1995	Taylor	128/897
5.568.384 A	*	10/1996	Robb et al	715/532

5,951,475 A	*	9/1999	Gueziec et al.	 600/425
6,301,495 B	1 *	10/2001	Gueziec et al.	 600/407
6,415,171 B	1 *	7/2002	Gueziec et al.	 600/407

OTHER PUBLICATIONS

Taylor et al., "An overview of computer-integrated surgery at the IBM Thomas J. Watson Research Center", 1996, IBM J. RE Develop. VOL 40 No. 2, pp 163–183.*

Lin et al., "Image Fusion Technique for Head-Neck CT and SPECT Image Registration", 1996.*

Mouravliansky et al., "A New Method for the Elastic Registration of CT and MRI Head Images", 1999, IEEE.* Maurer, Jr. et al., "Registration of Head CT Images to Physical Space Using a Weighted Combination of Points and Surfaces", 1998, IEEE.*

(List continued on next page.)

Primary Examiner—Almis R. Jankus (74) Attorney, Agent, or Firm—Louis J. Percello, Esq.; McGinn & Gibb, PLLC

(57) ABSTRACT

A system and method for intra-operatively providing a surgeon with visual evaluations of possible surgical outcomes ahead of time, and generating simulated data, includes a medical imaging camera, a registration device for registering data to a physical space, and to the medical imaging camera, and a fusion mechanism for fusing the data and the images to generate simulated data, without correcting for distortion. The simulated data (e.g., such as augmented X-ray images) is natural and easy for a surgeon to interpret. In an exemplary implementation, the system preferably includes a data processor which receives a threedimensional surgical plan or three-dimensional plan of therapy delivery, one or a plurality of two-dimensional intra-operative images, a three-dimensional model of preoperative data, registration data, and image calibration data. The data processor produces one or a plurality of simulated post-operative images, without correcting for distortion, by integrating a projection of a three-dimensional model of pre-operative data onto one or a plurality of twodimensional intra-operative images.

26 Claims, 4 Drawing Sheets



